

Product Name :
Muffle Furnace**Product Code :**
ALABS-A67-139**Description :****Muffle Furnace**

Mild weight with ceramic fibre woolled insulation (as an alternative of brick insulation). The outer casing is fabricated from double walled thick P.C.R.C. sheet, reattached with thick perforated sheet on the underside component, painted with horny range enamel. Heating parts are product of wire and backed with the aid of excessive temperature cerwool insulation, which avoids lack of vitality. Temperature keep an eye on unit includes Power Regulator, outfitted in entrance of furnace with two pilot lamps. The equipment is full with one pyrometer, thermocouple, silver thermal fuse, primary lead with energy plug. To work on 220/230 volts or four hundred/440 volts A.C.. The vitality regulator dial is arbitrarily marked zero-a hundred place. This marking does no longer point out temperature. It signifies keep an eye on stage i.e. at Place "a hundred" most electrical energy is allowed to float to the furnace. At place "zero" minimal electrical energy is glide to furnace. Most Temp. is 950°C and dealing Temp. 900°C. For version of upper temperature the utmost Temp. is 1200°C and dealing temp. 1100°C.



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084