

Product Name :
Selective Ion Analyzer**Product Code :**
EEMEL77M0003**Description :**

Selective Ion Analyzer

Technical Specification :

- Measuring Ranges:

pH: -2.000 to +19.999, -2.00 to +19.99

mV: -999.9 to +999.9, -1999 to +1999

Temp: -23 to 221 °F (-5.0 to 105.0 °C)

ISE: 0.000 to 9.999 mg/l, 0.00 to 99.9 mg/l, 0.0 to 999.9 mg/l, or 0 to 1999 mg/l

- Measuring Resolution:

pH: 0.001, 0.01

mV: 0.1, 1

Temp: 0.2°F (0.1°C)

ISE: 0.001 mg/l, 0.01 mg/l, 0.1 mg/l, 1 mg/l

- Precision:

pH (+ pH units from the calibration point): +0.003 from 59 to 95 °F (15 to 35 °C), +0.01

mV: +0.2 from 59 to 95 °F (15 to 35 °C)

Temp: +0.1 (NTC 30); +0.5 from 32 to 59 °F (0 to 15 °C), +0.1 from 59 to 95 °F (15 to 35 °C), +0.2 from 95 to 131 °F (35 to 55 °C) (PT 1000)

- pH correction function: Manual from -4 to 266 °F (-20 to 130 °C)
- Usable ISE electrodes: Combination and single electrodes with connector according to DIN 19262
ISE calibration procedure: Two point calibration or three point calibration with standards suiting the sample
ISE slope ranges: ± 25 to 35 mV and ± 50 to 70 Mv

- Serial Interface

Baud Rate: Adjustable: 1200, 2400, 4800, 9600 Baud

Type: RS232, data output

Data Bits: 8

Stop Bits: 2

Parity: None

Handshake: RTS/CTS + Xon/Xoff

Cable Length: Max. 15m

- Ambient Conditions:

Storage: -13 to +149 °F (-25 to +65 °C)

Operation: 14 to 131 °F (-10 to +55 °C)

Climatic Class: 2

- Power:

Batteries: 4 x 1.5 V alkali-manganese batteries, type AA

Operational Life: approx. 3000 operating hours

- Mains:

The following applies to all plug-in power supplies:

Connection max. overvoltage category II

Input: 100 to 240 V ~ / 50 to 60 Hz / 400 mA

Output: 9 V = / 1.5 A

- Weight: 0.7 lbs (0.3 kg)

Size: 6.8x3.1x1.5 in (172x80x37 mm)



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084