



Product Name:

Universal Dynamometer

Product Code: ALABS-A43-098



Description:

Universal Dynamometer

Technical Specification:

- It has two parts: the electric dynamometer, and a motor drive and display unit.
- The dynamometer is an induction motor, trunnion-mounted to allow it to move freely against a strain gauge load cell.
- The Universal Dynamometer directly drives the Fluid Power machines.
- This means that the user has no need to fit or adjust the tension of belts and pulleys.
- The motor drive and display unit contains a variable-speed a.c. inverter drive and includes signal conditioning.
- · It digitally displays speed, torque and shaft power.
- An inductive sensor measures the shaft speed.
- The load cell measures the shaft torque.
- A precision-machined base plate holds the motor and its sensors.
- The base plate has location points to give accurate and repeatable alignment onto each Fluid Power module.

- The coupling between the Universal Dynamometer and all Fluid Power machines is a jaw-type coupling with a rubber element.
- The front of the motor drive and display unit has motor stop, start and speed controls.
- Outlets on the back of the unit give power for instruments supplied with the Fluid Power modules.
- This reduces the need for multiple mains connections and gives a neater and safer equipment arrangement.



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com **Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084