

Product Name :
Accelerated Curing Tank**Product Code :**
CVLE0010**Description :**

Accelerated Curing Tank

Technical Specification :

- This curing tank has been designed to accommodate 150mm / 70.6mm cube moulds and upto 36/72 cube mould can be cured in one go.
- Controlled 35° C or 100° C \pm 2° C Curing Temperature for concrete.
- Controlled 27° C \pm 2° C Curing Temperature for grey cement.
- The pump, drain valves and electrical equipment are housed in a compartment located at one end of the tank.
- The tank is heated by an immersion heater under normal conditions and refrigeration system for grey cement the temperature is controlled at 35° C or 100° C \pm 2° C / 27° C \pm 2° C, except for the 15 minutes after immersion of the freshly made specimens.
- This special curing tanks have been designed for hot water curing or steam curing in accelerated strength concrete.
- The interior is made from stainless steel.
- The tank is fully insulated, comes complete with a hinged lid, heater, thermostat and re-circulated pump.

- Provision of two removable racks allows free circulation of water around each mould.
- 24 Hour cycle from time of mixing.
- The electronic programmer can control up to four test cycles with different thermal gradients and curing time to a defined temperature value for a complete automatic curing cycle.
- The control panel include a 28 column thermal printer.
- 6/12 moulds of 150 mm / 70.6 mm size
- 12/24 moulds of 150 mm / 70.6 mm size
- 24/48 moulds of 150 mm / 70.6 mm size
- 36/72 moulds of 150 mm / 70.6 mm size



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084