

Product Name:

Axial Flow Pump Test Rig

Product Code:

EEMECH45M0059



Description:

Axial Flow Pump Test Rig

Technical Specification:

- In an axial-flow pump the pumping medium flows through the impeller in the axial direction.
- In axial-flow pumps, the pressure build-up is not achieved by the centrifugal force but like the aerodynamic principle, by the propeller blade.
- A temperature sensor measures the water temperature.
- The flow rate is measured with an electromagnetic flow meter.
- They are not self-priming and the propeller must always be covered by the pumping medium.
- Axial propeller pumps are used when high flow rates and a small head are needed.
- The closed water circuit means that the trainer can be used independently of the water system.
- The trainer is equipped with measuring elements for the pressures at the inlet and outlet of the pump.
- The typical areas of application for propeller pumps are drainage systems, wastewater treatment plants and cooling water supply systems.
- Pump Output: 1000W at 1000min-1

Max. Flow rate: 700L/min

Max. Head: 1,75m

Tank: 160L

flow rate: 0...1200L/min

Temperature: 0...100°C

Pressure (inlet): ±1bar

• Pressure (outlet): 0...0,6bar

Power Supply: 230V, 50Hz, 1 phase

Dimension: 1110x800x1380mm

Weight: approx.: 154kg



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com **Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084