▲ **ALTEC**[™]

Email : sales@equipmentsexporters.com Phone: +91-9311469084

Description : Robotized Station(6 DOF Robot Trainer) Technical Specification : Picture is only for reference, use Chinese 6 DOF robot The device adopts an operating platform constructed of industrial aluminum profiles, which has good stability and easy assembly. The robot adopts a multi-joint six-degree-of-freedom robotic arm that can perform motion control in any direction, driven by servo motors and stepper motors, and driven by harmonic reducers , Stable operation and high accuracy. Technical parameters: Single-phase three-wire AC220V input, power less than or equal to 2KW, dimensions 1500 * 750 * 1700mm Contents of the experiment Objective	Product Name : Robotized Station(6 DOF Robot Trainer)	Product Code : MCHT0034
Robotized Station(6 DOF Robot Trainer) Technical Specification : Picture is only for reference, use Chinese 6 DOF robot The device adopts an operating platform constructed of industrial aluminum profiles, which has good stability and easy assembly. The robot adopts a multi-joint six-degree-of-freedom robotic arm that can perform motion control in any direction, driven by servo motors and stepper motors, and driven by harmonic reducers , Stable operation and high accuracy. Technical parameters: Single-phase three-wire AC220V input, power less than or equal to 2KW, dimensions 1500 * 750 * 1700mm		
Technical Specification : Picture is only for reference, use Chinese 6 DOF robot The device adopts an operating platform constructed of industrial aluminum profiles, which has good stability and easy assembly. The robot adopts a multi-joint six-degree-of-freedom robotic arm that can perform motion control in any direction, driven by servo motors and stepper motors, and driven by harmonic reducers , Stable operation and high accuracy. Technical parameters: Single-phase three-wire AC220V input, power less than or equal to 2KW, dimensions 1500 * 750 * 1700mm	Description :	
Picture is only for reference, use Chinese 6 DOF robot The device adopts an operating platform constructed of industrial aluminum profiles, which has good stability and easy assembly. The robot adopts a multi-joint six-degree-of-freedom robotic arm that can perform motion control in any direction, driven by servo motors and stepper motors, and driven by harmonic reducers , Stable operation and high accuracy. Technical parameters: Single-phase three-wire AC220V input, power less than or equal to 2KW, dimensions 1500 * 750 * 1700mm	Robotized Station(6 DOF Robot Trainer)	
The device adopts an operating platform constructed of industrial aluminum profiles, which has good stability and easy assembly. The robot adopts a multi-joint six-degree-of-freedom robotic arm that can perform motion control in any direction, driven by servo motors and stepper motors, and driven by harmonic reducers, Stable operation and high accuracy. Technical parameters: Single-phase three-wire AC220V input, power less than or equal to 2KW, dimensions 1500 * 750 * 1700mm	Technical Specification :	
and easy assembly. The robot adopts a multi-joint six-degree-of-freedom robotic arm that can perform motion control in any direction, driven by servo motors and stepper motors, and driven by harmonic reducers, Stable operation and high accuracy. Technical parameters: Single-phase three-wire AC220V input, power less than or equal to 2KW, dimensions 1500 * 750 * 1700mm	Picture is only for reference, use Chinese 6 DOF robot	
1500 * 750 * 1700mm	and easy assembly. The robot adopts a multi-joint six-degree-of-freedom robotic arm that can perform motion control in any direction, driven by servo motors and stepper motors, and driven by harmonic reducers, Stable	
Contents of the experiment Objective		
	Contents of the experiment Objective	

Website: www.equipmentsexporters.com, Email: sales@equipmentsexporters.com Address: 75, Lajpat Nagar-IV, New Delhi-110024 Phone: +91-9311469084

