

**Product Name :**  
Centrifugal Pump Diesel Driven**Product Code :**  
WATER-SAN0046**Description :**

Centrifugal Pump Diesel Driven

**Technical Specification :**

Self-priming centrifugal pumping set, capacity 50 Cubic Meters per hour at around 2900 RPM, at 20 meter TMH for 1-m suction head.

The skid has pre- drilled holes to facilitate bolting it to a foundation.

The pump is coupled directly to a diesel engine of matching power requirement.

Mounted on a trolley with 2 wheels and a handlebar, it can also be mounted on a sturdy steel skid with carrying handles.

The pump casing, shaft and impeller are made from cast iron, and the water seal on the shaft is mechanical.

The engine is fitted with a speed control governor, a fuel tank with sufficient capacity for (2 - 3) hours of continuous normal operation

The suction inlet and discharge outlets are available in various diameters depending on the pumping capacity of the pump

These vary in size such as: 50, 65, 75, 100 and 150 mm.

When a specific pump is ordered the supplier will provide the most efficient diameter of inlet/outlet pipes with the pump.

An air-cooled, direct injection, diesel engine powers this range of pumps and is available in one of three choices of starting devices: rope starting, recoil starter, or electric starter with 12 volt battery and charging alternator.



## Equipments Exporters

**Website:** [www.equipmentsexporters.com](http://www.equipmentsexporters.com), **Email:** [sales@equipmentsexporters.com](mailto:sales@equipmentsexporters.com)

**Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084