


Product Name :
Salt Spray Chamber**Product Code :**
ALABS-A89-163**Description :****Salt Spray Chamber**

- It has the function to refill water automatically when water level is insufficient.
- The control instruments are mounted in one panel so it easy to operate and Clear at a glance.
- The thermometer is controlled by SSR with digital display in precision of 0.1.
- The test tank is heated directly by vapor so that the temperature rises fast and the stand by time shortened.
- The water spraying column equipped with the disperser has the functions to lead and adjust the reek and also has the function to make the falling reek even (the control).

Safety Devices

1. Water level controller 1 set
2. Lights for state warning: 3 pcs

3. Protection switches for over temperature: 2 sets

Spraying Modes:

- Nozzles (G): Glass nozzles. The accurate glass nozzles (brand Pyres)
- Quantity of spraying: 1~2mL/80C/1h (imported from America)

Application Temperature:

(1) Set the type according to the standards of CNS, JIS and ASTM:

The test method of salt water:

The lab: 35degC ±1degC

(2) The saturated air barrel: 47degC±1degC

The test method of corrosive resistant

(1) The lab: 50degC±1degC

(2) The saturated air barrel: 63degC±1degC



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084