

Product Name :
Automatic Tissue Processor**Product Code :**
ALABS-A107-009**Description :****Automatic Tissue Processor****Main Technical Data**

- Steps of processing tissue: 12 steps.
- Glass containers: 9 with capacity of 1.2 L each.
- Wax cups: 3 with capacity of 1 L each. Temperature range: 45~85 C \pm 3
- Process: Each cup working hours between 0-59 hr 59 min. Delay process: 0-59 hrs 59 min.
- Vertically reciprocal motion of tissue basket: 3 times/min.
- Tissue basket specification: Barrel tissue basket- \varnothing 95 x 80 mm. Layer nacelle- \varnothing 95 x 80 mm, Five layers.
- Weight: \varnothing 60 kg.
- External dimension: (diameter) 660 x (high)550 x 680(Tip top) mm.
- Rated voltage: 220 v, 50 Hz or 110 V, 60 Hz

Technical specification:Main Performance Characteristic

- Adopting computer to control whole work process, operate brief work stabilization.
- Having exchange jar and change place control draw perch, operate agility brief.
- If lose electric, alarm sounds to protect tissue in liquid.
- Adopting agitation dehydrate mode enhance reagent and paraffin penetration into tissues.
- Easy to use with screen display in English.
- Wide time range: delay time 59 hrs 59 min. The longest working hours for each container is 59 hr 59 min, Time design least interval is 1 min.
- Wax jars adopt constant temperature control system. Temperature precision high: defend pollution, defend canker.
- Adopting 9 slice 1.2 L medicine aquarium, at any moment observe tissue change at work.
- According to user's need to tailor standby electrical source, after power cut it can also work in great, working hours can reach 4-16 hours.



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084