

Product Name :
Model of Sedimentation Tank**Product Code :**
ALABS-A138-003**Description :****Model of Sedimentation Tank**

- A rigid acrylic settling tank of 80L capacity can be fed by a mains water or a slurry supply. Slurry is pumped from a 120L sump tank via a centrifugal pump. A sparging device in the sump tank keeps the slurry in suspension.
- Both supplies are fitted with a flow meter. Mains water flow meter range 0.5 – 5.0 litres/min; slurry flow meter range 0 – 2 litres/min.
- A dye injection system is incorporated to allow hydraulic tracer and flow visualisation studies.
- Measuring flow regimes using a dye tracer and comparison of these with idealised flow models.
- Effect of variables such as flow rate and baffle position on flow regimes.
- Measurement of sediment removal efficiencies.

Description:

Water is taken from the laboratory mains

supply and is fed to the settling tank via a flow meter. For studies of sedimentation, a slurry is prepared in a sump tank and pumped via a specially designed flow meter to join the fresh water stream just before entry to the settling tank.

A well-mixed slurry of known concentration and flow enters the tank uniformly under an inlet weir. This may be comparatively analysed by the Imhoff cone technique or more accurately by drying and weighing. The sump tank is continually agitated by a flow sparge device to prevent settling of solids during an experiment.

For hydraulic tracer and visualisation studies, an accurate dye injection system is provided. A known volume of dye solution is injected just before the entry to the settling tank.

Technical Details:

- Settling tank: 1000 x 400 x 200mm
- Sediment sump tank capacity: 120 litres Water flow meter range: 0.5-5l/min
- Sediment suspension flow meter range: 0-2l/min
- Pump flow rate: 25l/min at 5m head
- Motor: 0.1kW



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084