



Product Name:

Cyclone Separator

Product Code:

ALABS-A155-018



Description:

Cyclone Separator

A Cyclone Separator is a vertical

cylinder with the inlet stream introduced tangentially near the top, giving the suspension a spinning rotation in the cylinder. The centrifugal force acting on the particles tends to throw them radially to the sides of the cylinder as they spiral downward to a conical bottom where they are removed. A collector is fitted at the bottom & the induced draft blower is used to create the air stream. The classified air leaves the cyclone through a pipe extended down into the cyclone & passes through blower delivery side fitted with fine screen cloth bag to avoid dust expansion in the laboratory.

The setup consists of I.D. blower connected to discharge side of Cyclone Separator. A flow meter with manometer is provided to measure the flow rate of air. Pressure drop in the Cyclone is measured by water manometer. Solids are collected in the collector fixed at the bottom. The set-up is complete with flow

Experimentation:

- To study the performance of a given Cyclone.
- To study the effect of inlet gas velocity on overall efficiency

Utilities Required:

- · Material for Feed.
- Electric Supply: Single phase, 220 V AC, 1 kW.
- Floor Area 2 m x 1 m.
- Weighing Balance.

Technical Details:

CMalterie Setain Letos Steel, Dia 100mm

SMixteDiscStarigeeSiscSteel, suitable capacity with discharge control valve.

BIDWFeam Blower with 1 HP provided motor

AFridowmeteerswittenneantometer.

SolialssCallerottoPVC container fixed with Cyclone.

FBrægDouistlyContleadatoth fixed on exit of air.

Control panel Comprises of:

Standard make On/Off switch, Mains Indicator etc.

A good quality painted rigid MS Structure is provided to support all the parts.



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com **Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084