

**Product Name :**  
Kinematic Viscosity Bath**Product Code :**  
ALABS-A19-129**Description :****Kinematic Viscosity Bath**

Double walled, outer chamber made of G.I. – powder coated, with removable toughened Glass window panel, inner chamber made of S. S, FHP motorised stirrer for uniform temperature, Dual Display Microprocessor Based Digital Temp. Controller with PT-100 sensor. Temperature range from 5° C above ambient to 100° C., Control accuracy  $\pm 0.1^{\circ}\text{C}$ . Below ambient Viscosity Baths are fitted with Refrigeration system (Temperature Range : 10°C to 100°C). The Baths can accommodate 2 / 4 / 8 Viscometers with varying tank volumes.

Stainless steel bath

Temperature controller (Thermostatic/Digital)

Immersion electric heater

Constant speed Pump cum stirrer

Carriage holding up to three standard briquette moulds

Electric motor with gear mechanism

Stainless steel scale and pointer

Control Panel



## Equipments Exporters

**Website:** [www.equipmentsexporters.com](http://www.equipmentsexporters.com), **Email:** [sales@equipmentsexporters.com](mailto:sales@equipmentsexporters.com)

**Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084