

Product Name :
Flexural Testing Machine**Product Code :**
ALABS-A22-015**Description :****Flexural Testing Machine**

The machine consists of a motorized load frame. The lower platen has two rollers, the distance between which is adjustable. For 150 mm x 150 mm x 700 mm beam, the centre distance between the rollers is 600 mm, while it is 400 mm for beams of size 100 mm x 100 mm x 500 mm. The upper platen has also a pair of rollers whose distance is adjustable. It is 200 mm centre to centre, for 150 mm x 150 mm x 700 mm size beam and 133 mm for 100 mm x 100 mm x 500 mm size beam. Total capacity of the machine is 100 KN. 150mm dia pressure gauge of 0-100 KN x 1 KN least count to indicate load is fixed on the load frame. A separate electrically cum hand operated pumping unit housed in a cabinet is supplied. On/Off switch and a slow/fast lever to control rate of loading are fitted on the front panel of the pumping unit. A facility for hand operation is provided. A micro switch and relay fitted inside the pressure gauge protect the unit from over loading.

Hand operated version consists of a load frame. A small hand pumping unit is attached to the load frame. Since this is a hand operated light weight machine. It is useful for field laboratory also.

Optional Accessories at Extra Cost.

- Spare Oil seal
- Hydraulic Oil (tin of 5 ltrs)
- Beam Mould 10 X 10 X 50 cm
- Beam Mould 15 X 15 X 60 cm
- Beam Mould 15 X 15 X 70 cm
- Beam Mould 15 X 15 X 75 cm
- Trowel
- Concrete Scoop



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084