

Product Name :
RTD Studies In CSTR**Product Code :**
ALABS-A17-022**Description :****RTD Studies In CSTR**

Real reactors do not satisfy the idealized flow patterns, back mix flow or plug flow deviation from ideality can be due to channeling of fluid through the vessel, recycling of fluid within the vessel or due to the presence of stagnant region or pockets of fluid in the vessel. To predict the exact behavior of a vessel as a Chemicals reactor, RTD Of stimulus response technique is used. The setup consists of one feed tank through which water is fed to the reactor. The flow rate can be adjusted by operating the needle valve and measured by Rotameter. The magnetic drive pump is used for circulation of feed. The continuously stirred tank reactor made of Stainless Steel is provided for understanding the R.T.D. characteristics. A syringe is used for dosing the tracer in the C.S.T.R

Experiments:

- To plot RTD curve for a CSTR Using pulse tracer
- To determine the Dispersion No

Utilities Required:

- Water Supply & Drain
- Electricity Supply: 1 Phase, 220 V AC, 0.5 kW
- Instruments, Laboratory Glassware and Chemicals required for analysis as per the system adopted



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com

Address: 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084