



Product Name:

Energy Losses in Bend and Fitting

Product Code: ALABS-A43-055



Description:

Energy Losses in Bend and Fitting

- · Circuit with four bends of different radii
- Enlargement, contraction and gate valve, plus control valve
- Manometer board with 12 tubes plus differential pressure gauge
- Hand pump for pressurization of manometers
- Quick release fitting for easy connection to hydraulics bench
- Educational Software available as an option

Description:

- The equipment is mounted on a free-standing framework which supports the test pipework and instrumentation.
- The following typical pipe fittings are incorporated for study: mitre bend, 90° elbow, sweep bends (large and

small radius), sudden contraction and sudden enlargement.

- All are instrumented with upstream and downstream pressure tappings.
- These tappings are connected to a bank
 of twelve water manometer tubes, mounted on the framework.
 Pressurisation of the manometers is facilititated by a hand pump.
- A gate valve is used to control the flow rate. A separate gate valve is instrumented with upstream and downstream pressure tappings which are connected to a differential gauge on the edge of the framework.

_			
$1 \wedge \wedge$	hnical	l Detail	
166	ııııca	ı Delai	ъ.

Mahae

P9048dinameter:

Diffoed domainal pressure gauge:

E6.12 ingrement diameter:

Con 48 aution diameter:

F46thmostre

-elbow

-short bend

-large bend

-enlargement

-contraction

Mten 440ettern range:

Mumber of manometer tubes:

Differential manometers:



Equipments Exporters

Website: www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com **Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084