

**Product Name :**  
Centrifugal Governor Apparatus**Product Code :**  
ALABS-A104-219ALTEC™**Description :****Centrifugal Governor Apparatus**

Centrifugal governors use the properties of centrifugal force to regulate the speed of a machine. Due to centrifugal force, a rotating flyweight mass has the tendency to move away from the axis of rotation and is prevented by counteracting mechanisms. These mechanisms are differentiated into those governors that use weights and those that use springs. Corresponding kinematics cause a deflection proportional to the rotational speed to occur on the governor. Via an actuator, this affects the energy supplied to the machine, thereby regulating the machine's speed. The experimental unit presents centrifugal systems that demonstrate the different principles of operation of both weight and spring-based governors. The housing holds the drive with electronically controlled motor. The speed is infinitely variable with a 10-turn potentiometer and displayed digitally. The governors are inserted into a chuck on the drive. Centrifugal masses, sleeve forces and spring preload can be varied using the accessories supplied, depending on the governor. The stroke can be read on markings on the governor shaft. A transparent protective cover above the rotating centrifugal governor ensures safety: operation is only possible when the protective cover is properly attached.

**Specification:**

1. Three different centrifugal governors: Porter, Proell and Hartnell governors
2. Versatile range of variations on the governors: adjustment of the centrifugal mass, the sleeve force and the spring preload
3. Stepless adjustment of speed via a potentiometer
4. Drive with DC motor
5. Digital speed indicator
6. Protective cover with electronic coupling to the drive ensures safe operation

**Technical Data:***DC motor:*

- max. power 35W
- max. speed  $6000\text{min}^{-1}$

Speed regulation  $60\ldots400\text{min}^{-1}$

*Proell governor:*

- sleeve mass  $3 \times 100\text{g}$
- centrifugal mass  $2 \times 150\text{g}$

*Porter governor:*

- sleeve mass  $3 \times 100\text{g}$
- centrifugal mass  $2 \times 400\text{g}$

*Hartnell governor:*

- centrifugal mass  $2 \times 400\text{g}$
- 2 compression springs, adjustable spring preload

*Measuring range*

- speed:  $0\ldots600\text{min}^{-1}$



## Equipments Exporters

**Website:** [www.equipmentsexporters.com](http://www.equipmentsexporters.com), **Email:** [sales@equipmentsexporters.com](mailto:sales@equipmentsexporters.com)

**Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084