



**Product Name:** 

Refrigeration Trainer

Product Code: ALABS-A36-030



## **Description:**

## **Refrigeration Trainer**

#### **Refrigeration Trainer allows**

students & industry professionals to learn the fundamentals of Simple Vapour Compression Refrigeration System. The design of this Refrigeration Training System is to allow the user to study this Technology in great detail. The training system introduces various sub-systems with real components. The training system brings a comprehensive view of the entire Refrigeration system. Actual component study and their interconnection, functions, operation, diagnosis, etc. are a part of the scope of training. The construction of the trainer is on a main platform unit mounted on a trolley. This helps the students to place the trainer at their desired position. However, the height of the trainer is as

such, the students can comfortably observe the reading while performing the experiments. The unit is opened, in order to provide an open exposure to the students for understanding the importance of each component in the process cycle. In this trainer, students can learn how to calculate the Coefficient of Performance (C.O.P.) of a compressor, based on which he / she can know the capacity of a compressor. Apart from this, students are also able to know the power consumed by the

compressor. The front panel also includes Toggle Switches, LCD, Pressure Dials, Voltmeter and Ammeter.

#### Features:

- Refrigerant (R134) used is non-poisonous, harmless to body and eco-friendly
- Compact and Self-contained
- Mounted on trolley for mobility
- Digital LCD for Temperature
- Multi point temperature measurement
- Process Diagram on front panel
- Easy component identification

#### **Technical Specifications:**

- Condenser: 10 11 2 Turns
- Motor: 230 V AC 50 Hz, 0.40 Amps, 9 watt and 1360 RPM
- Evaporator & Tank: Capacity: 20 litres
- Compressor: 1/3 HP, 925 BTU, 150 watt, R134a (Refrigerant), 220 V AC 50 Hz,
- Drier: 1/4- Threaded (male)
- Pressure Gauge (P1, High): 0 300 PSIG & 0 21 kg / cm2
- Pressure Gauge (P2, Low): -30 to 150 PSIG
- Ammeter: 0 to 5 Amps AC
- Voltmeter: 0 to 300 V AC
- Pump: Submersible, 220 VAC, 800 L/H
- Heater: 220 VAC, 50 Hz, 500 watt
- Rotameter: 0 to 30 LPM, Acrylic body

- LCD: 16′2
- Temperature Range: 0° -100°C

### Scope of Learning:

- To study the Simple Vapour Compression Refrigeration System (SVCR)
- To calculate the Co-efficient of Performance (C.O.P)
- To calculate the power consumption of the compressor



# **Equipments Exporters**

**Website:** www.equipmentsexporters.com, **Email:** sales@equipmentsexporters.com **Address:** 75, Lajpat Nagar-IV, New Delhi-110024 **Phone:** +91-9311469084